


















**MADE IN
TAIWAN**

PROMO








Réf.	Specification	Image	Prix HT
DVR-9306EH DVR 16 ch HDMI	<p>Support HDMI,TV,VGA,simultaneously video output.</p> <ul style="list-style-type: none"> • Simultaneously 16 ch full-real time record & network-transmission,16ch support 2ch D1+14ch CIF simultaneously playback,8ch support 4ch D1+4ch CIF simultaneously playback,4ch support 4ch D1 simultaneously playback,and 16ch CIF/QCIF sub-code stream achieve standard H.264 coding. • Zoom function in both preview & palyback. • Support UPNP,Built-in free DDNS. • Support P2P function,support 3G dongle. • Support multi-languages. • Support multi-code stream technology,and mobile phone surveillance(Iphone,android,symbian,windows and blackberry) 		2 900,00
DVR-7808EH DVR 8 ch HDMI	<p>Support P2P function, Support 3G dongle</p> <ul style="list-style-type: none"> • Simultaneously 16/8/4ch full -real time record & network-transmission & playback, 16/8/4ch CIF/QCIF sub-code stream • Zoom function in both preview & playback • High-perfomance CPU, support HDMI, TV, VGA simultaneously Vido output • Support UPNP, Built-in free DDNS • Support Multi-languages • Support Muiiti-code stream technology, and mobile remote surveillance (Iphone, Symbian, Blackberry, Android,Windows) • Support 1 SATA HDD, support E-SATA, 		1 800,00
DVR-7804EH dvr 4 ch HDMI	<p>Support P2P function, Support 3G dongle</p> <ul style="list-style-type: none"> • Simultaneously 16/8/4ch full -real time record & network-transmission & playback, 16/8/4ch CIF/QCIF sub-code stream • Zoom function in both preview & playback • High-perfomance CPU, support HDMI, TV, VGA simultaneously Vido output • Support UPNP, Built-in free DDNS • Support Multi-languages • Support Muiiti-code stream technology, and mobile remote surveillance (Iphone, Symbian, Blackberry, Android,Windows) 		1 400,00

9032A DVR 32 CH HDMI	<ul style="list-style-type: none"> • High-performance CPU,support HDMI,VGA,CVBS output • Zoom function for both preview and playback • Have the function of picture-in-picture(PIP) • All the channels support D1 real-time coding • Graphical operating interface,support mouse,panel snd remote control operation • Support varied PTZ control protocol,and embedded web visiting,support HTTP,SMTP,DDNS,DHCP,PPPOE and NAT traversing. • Loop-out function(optional) • Support mobile surveillance • Built-in free Dynamic DNS 		9 800,00
TP-1000YXND	1/3" SONY CMOS138 Powerful High Resolution: 1000 TVL 8pcs IR Array LED; IR Distance:20-25M VF Lens: 2,8-12mm With IR-CUT		890,00
TP-1000IR-H	1/3" SONY CMOS138 Powerful High Resolution: 1000 TVL 8pcs IR Array LED; IR Distance:40M VF Lens:2,8-12mm With IR-CUT		950,00
TIS-617S7	1/3.7" HDIS Sensor PAL:752(H)×582(V) High Resolution: 800TVL 35 pcs IR LED,IR Distance: 30M Board Lens:3.6mm;with IR-CUT IR ON 0 Lux		750,00
DIS-735ST2	1/3" SONY Exmor CMOS High Resolution: 1,200TVL 8pcs IR Array LED; IR Distance:40-60M VF Lens: 6-22mm With IR-CUT		1 100,00
DIS-9368ST2	1/3" SONY Exmor CMOS High Resolution: 1200TVL 4pcs IR Array LED; IR Distance: Max.100M VF Lens:6-22mm;IP-rated 66		1 600,00
LVDC45XSHE	<ul style="list-style-type: none"> • 1/3" SONY 700TVL, Low Illumination, DWDR, OSD, DNR Effio-E • Lens 2.8-12mm Auto Zoom Lens (2M Pixels) • IR Series Distance 25 M • Controlled by RS485 		1 050,00

TP-D315HS	CMOS 1/3" NTSC:1296x1041, PAL:1296x1041 1000TVLines CDS auto control Lens: 3,6mm IR Project Distance: 20m 0 lux with IR LED ON		790,00
TP-A316HS	CMOS 1/3", OSD, DNR, DWDR• Resolution: 1000TVL • Color:0.03Lux / B/W:0.01Lux• 5X35pcs IR LED, IR Range: 50M with 2 unit infrared LED 2.8-12mm/F1.2 Manual		890,00
TP-D210HS	CMOS 1/3" NTSC:1296x1041, PAL:1296x1041 1000TVLines CDS auto control Lens: 3,6mm IR Project Distance: 15m		690,00
TP-S430HDZ	Sony 1/3" Color CCD 650 TVLines Angle of View Wide:46° TELE:4.6° BNC 1,0Vp-p/75 Ω DC12V Auto flip rotate 180 when camera tilts to the vertical position Pan speed manuel: 120°/s preset position: 300°/s Tilt speed auto: 90°/s preset position: 300°/s Pan range 360° continuously rotation Optical zoom 10X Digital Zoom 10X		2 900,00
TP-YC-736IR	Sony 1/3" Color CCD 700 TVLines Angle of View Wide:46° TELE:4.6° BNC 1,0Vp-p/75 Ω DC12V Auto flip rotate 180 when camera tilts to the vertical position Pan speed manuel: 120°/s preset position: 300°/s Tilt speed auto: 90°/s preset position: 300°/s Pan range 360° continuously rotation Optical zoom 36X		8 900,00
TP-YC-712HSP9016	Sony 1/3" Color CCD 700 TVLines Angle of View Wide:46° TELE:4.6° BNC 1,0Vp-p/75 Ω DC12V Auto flip rotate 180 when camera tilts to the vertical position Pan speed manuel: 120°/s preset position: 300°/s Tilt speed auto: 90°/s preset position: 300°/s Pan range 360° continuously rotation Optical zoom 27X		6 900,00
MG6HU125F	Sony 1/4" Color CCD 720 TVLines Angle of View Wide:46° TELE:4.6° BNC 1,0Vp-p/75 Ω DC12V Auto flip rotate 180 when camera tilts to the vertical position Pan speed manuel: 120°/s preset position: 300°/s Tilt speed auto: 90°/s preset position: 300°/s Pan range 360° continuously rotation Optical zoom 12X Digital Zoom 12X		3 200,00

TP-797FAHBB61	CMOS 1/3" NTSC:1296x1041, PAL:1296x1041 1000TVLines CDS auto control Lens: 3,6mm IR Project Distance: 20m 0 lux with IR LED ON		590,00
TP-797FAHZ37	1/3.7" HDIS Sensor PAL:752(H)×582(V) High Resolution: 1000TVL 35 pcs IR LED,IR Distance: 30M Board Lens:3.6mm;with IR-CUT IR ON 0 Lux		590,00
TP-797FAHZ80	1/3" SONY CMOS138 Powerful High Resolution: 1000 TVL 8pcs IR Array LED; IR Distance:60M VF Lens: 2,8-12mm With IR-CUT		795,00
TP-797FAHZ52	1/3" SONY CMOS138 Powerful High Resolution: 1000 TVL 8pcs IR Array LED; IR Distance:60M VF Lens: 2,8-12mm With IR-CUT		790,00
TP-797FAHBB71	CMOS 1/3", OSD, DNR, DWDR• Resolution: 1000TVL • Color:0.03Lux / B/W:0.01Lux• 5X35pcs IR LED, IR Range: 50M with 2 unit infrared LED 2.8-12mm/F1.2 Manual		750,00
TP-797FAHBB85V	1/3.7" HDIS Sensor PAL:752(H)×582(V) High Resolution: 1000TVL 35 pcs IR LED,IR Distance: 30M Board Lens:3.6mm;with IR-CUT IR ON 0 Lux		600,00
LPRCSHE	<ul style="list-style-type: none"> • SONY Color CCD 700 TVL • Smoke Detector Camera • Auto White Balance(AWB) • Lens:3.6mm Board Lens 		600,00

LSDCSHE	<ul style="list-style-type: none"> • SONY Color CCD 700 TVL • Smoke Detector Camera • Auto White Balance(AWB) • Lens:3.6mm Board Lens 		600,00
CMSH/40	<p>1/3" Sony Super HAD II Color CCD Sensor Built-In Lens: 4.3mm Lens Angle : 78° System :NTSC : 811 (H) x 508 (V) PAL : 795 (H) x 596 (V) Resolution :540 TV Lines Minimum Illumination: 0.1 Lux</p>		1 490,00
CMOH/40	<p>1/3" Sony Super HAD II Color CCD Sensor Built-In Lens : 4.3mm Lens Angle : 78° System : NTSC : 811 (H) x 508 (V) PAL : 795 (H) x 596 (V) Resolution : 540 TV Lines Minimum Illumination : 0.1 Lux</p>		1 490,00
SDK65	<p>Security Speed Dome Camera 3D Keyboard Controller. Using 3 axis joystick to control the Pan/Tilt direction and speed of the dome camera. Up to 32 speed dome cameras. 2000 feet maximum distance communication. Maximum of 255 addressable preset points and 1~6 tours. Using EIA/RS-485 electrical interface between the keyboard and the the receive</p>		1 950,00
PIH-931D	<p>Joystick: 3 Axis (Pan/ Tilt / Zoom) Movement Speed control: Pan 8 Steps Tilt 8 Steps Zoom 16 Steps Data Communication: RS-485 Standard(Format N, 8, 1, Baud rate 9600bps) Connector: RJ-45 / 8Pin Control Mode: PTZ / MATRIX / DVR LCD Display: 20 Characters x 4 Lines Keyboard Keypad :Total 54 keys 0~9 Numeric keys</p>		3 900,00
S-12V4A-4L	<p>Boite d'alimentation 12 vdc sortie 4 cctv. switch mode power supply 4 amp de puissance de sortie, 4 x. 1000ma sorties tension d'entrée peut être sélectionné entre 110v et 220v</p>		390,00

TP-9604-POE	Kit Video IP POE - 4 camera IP Etanche 1,3 Megapixel , Qualité HD, PoE - 1 NVR 4 channel PoE switch, HDMI		4 500,00
S-12V10A-9L	Boite d'alimentation 12 vdc sortie 9 cctv. switch mode power supply 10 amp de puissance de sortie, 9 x. 1000ma sorties tension d'entrée peut être sélectionné entre 110v et 220v		650,00
BNC	Connecteur BNC a sertir 100% cuivre		7,00
PS	Fiche d'alimentation Male		6,00
SO500V	Onduleur Stabilisateur Eaton Nova AVR 500 VA		450,00
KX6	Câble coaxial 75 Ohm spécial vidéo surveillance KX6 la marque d'Italie 100% Cuivre		3,40
T1-zks-opt	Various data transmission methods, such as RS485, TCP/IP, USB, 2.8 inches TFT color LCD, Build in backup battery , Verification Method FP, PWD, Card , Optical Sensor with high sensibility, Transaction Records 80 000, Fingerprint Capacity 3000		3 900,00



Kit Alarme sans fil Mix RTC+GSM connexion 220v:

- ✓ 1- Centrale Alarme sans fil 220v
- ✓ 1 - Batterie de secours 12V24Ah
- ✓ 1 - Double transmetteur téléphonique RTC+GSM
- ✓ 1 - Télécommande
- ✓ 1 - Contact magnétique
- ✓ 1 - Détecteur infrarouge pour l'intérieur

4900 DH /ht

Périphériques Optionnels :

- ✓ 1 - Sirène radio pour l'intérieur 433MHz : **650 DH/ht**
- ✓ 1 - Sirène radio pour l'extérieur : **900 DH/ht**
- ✓ 1 - Clavier bidirectionnel sans fils : **450 DH/ht**
- ✓ 1 - Détecteur de mouvement pour L'extérieur : **450 DH/ht**

Tél : 05 22-52-67-11 / 05 22-50-03-50

Fax : 05 22-52-67-12 **Gsm :** (+212)06 62 730 408
(+212)06 61 15 15 45

E-mail : s.commercial@gegaformix.ma

Adresse: Rue 202 N° 33, Hay Moulay Abdellah BV Al Qods,
Casablanca, MAROC.

<http://www.sonycam.ma>

N° CB178 780 212119013810004 66 Bq Populaire, Agence Smara Casablanca.