












MODEL	Picture	Parameters	Sample
Fingerprint Time Attendance System			
T20U		3,000 fingerprint templates; RS485; USB; TCP/IP Options: EM or Mifare Card reader; Battery	
T21U		3,000 fingerprint templates; RS485; USB; TCP/IP Options: EM or Mifare Card reader; Battery	
Fingerprint Time Attendance and Simple Access Control System			
T1		3,000 fingerprint templates; RS232; Access Control Options: EM or Mifare Card Reader; Battery	
T2		3,000 fingerprint templates; RS232; TCP/IP; Access Control Options: EM or Mifare Card Reader; USB; Battery	
T1B-S		3,000 fingerprint templates; RS232; TCP/IP; Access Control Options: EM or Mifare Card Reader; USB; Battery	
T1B-B		3,000 fingerprint templates; RS232; TCP/IP; Access Control Options: EM or Mifare Card Reader; USB; Battery	
T1B-W		3,000 fingerprint templates; RS232; TCP/IP; Access Control Options: EM or Mifare Card Reader; USB; Battery	
T2B		3,000 fingerprint templates; RS232; TCP/IP; Access Control Options: EM or Mifare Card Reader; USB; Battery	


T3-B		3,000 fingerprint templates; RS232; TCP/IP; Access Control Options: EM or Mifare Card Reader; USB; Battery	
T3-G		3,000 fingerprint templates; RS232; TCP/IP; Access Control Options: EM or Mifare Card Reader; USB; Battery	
T22		3,000 fingerprint templates; USB; TCP/IP; Access Control Options: EM or Mifare Card Reader; USB; Battery	
T23		3,000 fingerprint templates; RS232; TCP/IP; Access Control Options: EM or Mifare Card Reader; USB; Battery	
T24		3,000 fingerprint templates; RS232; TCP/IP; Access Control Options: EM or Mifare Card Reader; USB; Battery	
T25		3,000 fingerprint templates; RS232; TCP/IP; Access Control Options: EM or Mifare Card Reader; USB; Battery	
TFT Color Fingerprint Time Attendance and Simple Access Control System			
iColor7^{NEW}		ARM9-VPN; 3,000 fingerprint templates; <0.6; USB; TCP/IP; Options: Battery; EM or Mifare One card reader	
iColor8^{NEW}		ARM9-VPN; 3,000 fingerprint templates; <0.6; USB; TCP/IP; Access Control EM or Mifare one card reader	
RFID Time Attendance and Simple Access Control System			
T22C		10,000 card templates; RS232; TCP/IP; Access Control Options: Battery; USB; Mifare one card raeder	

T23C		10,000 card templates; RS232; TCP/IP; Access Control Options: Battery; USB; Mifare one card reader	
Multimedia Fingerprint Time Attendance and Access Control System			
T8		ARM9-VPN; 60MB memory, 3.5-inch TFT LCD, Linux system TCP/IP; RS485; USB; EM or Mifare card; Camera Options: SD card; Backup Battery; external card reader; GRPS	
T9		ARM9-VPN; 3,000 fingerprint templates; 60MB memory, 3.5-inch TFT LCD, Linux system TCP/IP; RS485; USB; Camera Options: SD card; Backup Battery; external card reader; GRPS	
Multimedia Facial Time Attendance System			
F10 <small>New</small>		Unlimited face templates; 3.0 Touch TFT LCD; TCP/IP; USB; RS485 ; Proximity card reader Options: Mifare one card Reader	
Multimedia Facial Access Control and Time Attendance System			
F20 <small>New</small>		Safe metal shell; unlimited face templates; 3.0 Touch Black LCD; TCP/IP; RS485; Proximity card Reader; Access controller; Group and	
Fingerprint Access Control and Time Attendance System			
A3		3,000 fingerprint templates; TCP/IP; USB; RS232; Group and time	
A2 Special Price		3,000 fingerprint templates; TCP/IP; RS232; Group and time zone	



Fingerprint Door Lock

L1/L1G		110 fingerprint templates	
L2/L2G		60 fingerprint templates	




Fingerprint USB Sensor






ZKS1000		1,000 fingerprint templates; optical fingerprint sensor; USB port Options: 5000 Fingerprints: 10000	
----------------	---	---	--

Fingerprint module

M1		120 fingerprint templates for door lock and safe; optical fingerprint sensor; DSP processor	
M2		Sensor ; 508DPI; CMOS capacitive TouchChip™	

Accessories

Proximity/EM card		Code: 64bit Resonance frequency: 125 KHz operating temp. Range: -10 to +50 degree	1~999 units
Mifare one card		Standard version (1KBytes, 8KBites) Resonance frequency: 13.56MHZ Operating temp. Range: -10 to +50 degree	1~999 units
Access Controlle		Four-door and one-way; TCP/IP; 20,000 card templates; Black metal shell	Model: ZKS-B04

Proximity card reader		Support Weigand 26/34; Proximity card; Punch keypad	Model: YSD-069E
Plug Electronic		Dark installation; Lock up on Electricity, magnetic Induction; DC12Vinput; 350mA; 200*	Model: EC200B
UPS with Power Supply of access control		Export lock control signal; Export NO/NC doors 	Model: UPS
Patrol Stick		8000 records storage capacity, Leathery shell	Model: ZKS-P1000-8A